


Professional tools

for the construction craftsman



info@multitool.de · www.multitool.de



Size Table

Radiator Brush	Size	1/2"	3/4"	1"	1 1/2"	2"	2 1/2"	3"	4"
	width mm	12,5	18	25	38	50	62	75	100

Flat Brush	Width	15 mm	25 mm	40 mm	50 mm	60 mm	75 mm	85 mm	100 mm
	1. Grade / mm	4	4,5	4,5	5	5,5	6	6,5	6,5
	2. Grade / mm	5,5	6	6,5	7	7,8	8	9	9
	3. Grade / mm	6	7	7,5	8	9	9,5	10	10,5
	4. Grade / mm	7	8	9	10	11	12	12,5	13
	5. Grade / mm	8	9	10	11	12	13	14	15
	6. Grade / mm	10	11	12	13	14	15	16	17
	7. Grade / mm	11	12	13	14	15	16	17	18
	8. Grade / mm	12	13	14	15	16	17	18	19
	9. Grade / mm	13	14	15	16	17	18	19	20
	10. Grade / mm	14	15	16	17	18	19	20	21
	12. Grade / mm	-	17	18	19	21	22	23	23

Ring Brush	Size	2	4	6	8	10	12	14	16	18
	Ø mm	20	25	30	35	40	45	50	55	60



	Item	Item-No.	Package/Piece	Piece/Pair
Contents Pag	e Contents			Page
Covering roll				
Waste Bag, blue and transparent 5				
Stripping Plier				
Barrier Tape				
Grid				
Wallpaper(ing) ? Brush				
Wallpaper Roller				
Wallpaper Towel				
Floor Grounding Kit				
Working- and Protecting Clothes				
Dust Respirator				
Construction Lamp (Halogen)				
Brooms				
Concrete testing hammer				
Bit Set				
Pencil		•		
Drill Set	9			
Core Drill Bit				
Roller Handles				
Cutter Knife	8 Roller Box			33
Diamand Blades 6				
Diamond Grinding Cup Ø 115 to 300mm $\dots \dots 61$ to 6				
Diamond Grinding Cup Ø38 to 43cm				
Wire Brush	_			
Buckets				
Mop				
Disposable Clothing				
Laser Distancemeter				
Spiked Roller 3 Screed Clips 6				
Screed Shoes				
Paint Roller				
Paint Scraper				
Paint Tray- and Bucket				
Evacuation Cock				73
Barrel Plug Key	8 Sponges			26
Barrel Cart and Dump 78 to 7				
Material Moisture Meters				
Varnish Roller "Flock"				
Joint Board and Joint Rubber				
Joint Cleaner				
Floor Scraper				
Grid Plate				
Rubber Squeegee				
Pull Off Tester automatic				
Pull Off Tester manual				
Hammer				
Hand Brush	0 Wallpapering Brush	1		10
Lever Press				
Gloves	,			
Hand Support	_			
Skin Lotion				
Radiator Roller				
Bucket Carrier				
Concave, Triangle Trowel	0 0			
Pyrometer				
Injectec Accessories				
Cable Detector				
Cable Drum				
Cartouche Pistol				
Road Sweeper				





Item	Item-No.	Package/Piece	Piece/Pair

Radiator Brush Industry Quality

pure light Chinese bristles, for cleaning purpose

1"	011.010	12	
		360	
1,5"	011.015	12	
		300	
2"	011.020	12	
		240	
2,5"	011.025	12	
		180	
3"	011.030	12	
		120	



Radiator Brush Top Industrie Quality

pure grey Chinese bristles

,			
1"	011.110	12	
		360	
1,5"	011.115	12	
		300	
2"	011.120	12	
		240	
2,5"	011.125	12	
		180	
3"	011.130	12	
		120	



Radiator Brush Master Quality

pure black Chinese bristles

1"	012.010	12
		360
1,5"	012.015	12
		300
2"	012.020	12
		240
2,5"	012.025	12
		180
3"	012.030	12
		120



Radiator Brush Top Quality (Made in Germany) pure light Chinese bristles

, .		
1"	012.110	12
		360
1,5"	012.115	12
		300
2"	012.120	12
		240
2,5"	012.125	12
•		180
3"	012.130	12
		120





				_	
ltem			Item-No. P	ackage/Piece Piece/F	Paiı
	_	_			

Facade Brush

pure light Chinese bristle 56mm, untreated wooden handle

2"	012.620	12	
		180	
3"	012.630	12	
		120	
4"	012.640	12	
		96	



Thin Brush

angeled, pure black Chinese bristles

10 mm	013.010	12
15 mm	013.015	12
20 mm	013.020	12
25 mm	013.025	12
30 mm	013.030	12



Silverpren Ceiling Brush

special Silverpren filling, punched in bundles, plastic handle with thread and bucket hook, solvent resistant

18 x 8 cm	014.020	6
		12



Universal Ceiling Brush

Synthetic bristles, light coat, dark insertion, punched in bundles, plastic handle with thread and bucket hook

17 x 7 cm	014.030	6
		10



Professionel Ceiling Brush

pure light Chines bristle approx. 89cm long

18 x 8,5 014.035	1
------------------	---



Oval Paint Brush, Premium Quality

premium quality, pure light Chinese bristle

7 x14 cm	014.214	1

Item	Item-No.	€ Package/Piece Piece/	Dair
Ceiling Fibre Brush Heatproofed Fibre bristles 7x17 cm 8x17,5 cm	014.040 014.041	12 12	
Tar Scrubber white fibre 7 x 23 cm	014.042	12 24	
Floor Painting Brush approx. 60mm long pure C 21 x 3 cm 30 x 3 cm	ninese bristles, vu 014.052 014.053	lcanized, with handlebrac 1 1	ket
Wall Brush light Chinese bristles, plast 3 x 7 cm 3 x 10 cm 3 x 12 cm	ic handle with thr 014.048 014.049 014.050	ead and bucket hook 6 60 6 60 6 60	
Block Brush 90% Tops, light Chinese br 2,4 x 8 cm 2,6 x 10 cm 2,8 x 12 cm 3,0 x 14 cm	istles, Master Qua 014.080 014.100 014.120 014.140	lity, untreated wooden har 6 6 6 6 6	ndle
Flat Brush pure light Chinese bristles, 1th Grade 1" Thickness 4,5 mm 1,5" Thickness 5 mm 2" Thickness 5,5 mm 2,5" Thickness 6 mm 3" Thickness 6,5 mm 4" Thickness 6,5 mm	untreated wooder 015.210 015.215 015.220 015.225 015.230 015.240	12 12 12 12 12 12 12	





016.040

Thickness 21 mm

6



			_
Item	Item-No.	Package/Piece	Piece/Pai

Flat Brush

top quality, pure light chinese bristles, untreated wooden handle, 12th Grade

1"	016.110	12	
Thickness 18 mm		120	
1,5"	016.115	12	
Thickness 19 mm		120	
2"	016.120	12	
Thickness 21 mm		120	
2,5"	016.125	12	
Thickness 22 mm		120	
3"	016.130	12	
Thickness 23 mm		120	
4"	016.140	6	
Thickness 23 mm		60	



Flat Brush for acrylics

High quality Orel-Mix bristles, untreated wooden handle, 10th Grade

VBL = Visuable Brush Length

30mm VBL 50mm	016.830	12
40mm VBL 50mm	016.840	12
50mm VBL 50mm	016.850	12
60mm VBL 60mm	016.860	12



Flat Brush for acrylics

Polymix bristles, plastic handle, 6th Grade

VBL = Visuable Brush Length

20mm VBL 45mm	016.520	12 120
25mm	016.525	12
VBL 45mm	016.535	120 12
35mm VBL 51mm	010.555	120
50mm	016.550	12
VBL 51mm		120
60mm	016.560	12
VBL 56mm		120
70mm	016.570	12
VBL 56mm		120
100mm	016.599	12
VBL 62mm		60



Round Brush

Industry Quality, white rope, pure light Chinese bristles **VBL** = Visuable Brush Length

2 ø20mm	017.002	12
VBL 60 mm		120
4 ø25mm	017.004	12
VBL 65 mm		120
6 ø30mm	017.006	12
VBL 65 mm		120
8 ø35mm	017.008	12
VBL 70 mm		120
10 ø40mm	017.010	12
VBL 75 mm		120
12 ø45mm	017.012	12
VBL 80 mm		120









Item Item-No. Package/Piece Piece/Pair

Dusting Brush

pure light Chinese bristles, in row vulcanized, untreated wooden body

17cm

014.055

12



Wallpapering Brush

Synthetic bristle forhead-beared, punched in bundles, untreated wooden body

20 x 6 cm

020.020

3



Wallpapering Brush

pure horse hair double bounded-bearded, extra thick quality, punched in bundles, untreated wooden body

23,5 x 6 cm

020.021

3



Paperhanging Brush

Synthetic bristle, punched in bundles, untreated wooden body with handle hole

30 x 2,5 cm

020.030

3



Primer Roller (Vestan)

Pile Height 18mm, Core Ø 48 mm for primer works

not padded (for smooth surfaces)

width

180 mm	10.018.001	10
		100
250 mm	10.000.001	10
		100
400 mm	10.040.001	1
		10
500 mm	10.050.001	1
		10



Primer Roller (Vestan)

Pile Height 18mm, Core Ø 48 mm for primer works

padded (for rough surfaces)

width

180 mm	10.018.002	10
		100
250 mm	10.000.002	10
		100


Piece/Pair

Package/Piece



Item





Pile Height 18mm Core Ø 48 mm

not padded Width

250 mm 10.900.001 10 100

Item-No.



Varnish Roller Nylon (Premium Quality)

Pile Height 6 mm

solvent resistant suitable for primers, sealents, varnishes, oil paints, liquid plastics, epoxy and 2-components paints, for finish coating Core \emptyset 48 mm

Width		
180 mm	10.118.006	10
		100
250 mm	10.100.006	10
		100
500 mm	10.150.006	1
		10



Varnish Roller Nylon (Premium Quality)

Pile Height 8 mm

blue/blue thread, for topcoat application on smooth surfaces Core \emptyset 48 mm

Width		
180 mm	10.118.008	10
		100
250 mm	10.100.008	10
		100
400 mm	10.140.008	1
		10
500 mm	10.150.008	1
		10
600 mm	10.160.008	1
		10



Varnish Roller Nylon (Standard Quality)

Pile Height 8 mm

green/black thread, for topcoat application on smooth surfaces Core Ø 48 mm

Width		
250 mm	10.101.008	10
		100




Varnish Roller Nylon (Premium Quality)

Pile Height 12 mm,

for topcoat application on smooth surfaces and slightly rough surfaces Core \emptyset 48 mm

00.0 5 .0			
Width			
180 mm	10.118.012	10	
		100	
250 mm	10.100.012	10	
		100	
400 mm	10.140.012	1	
		10	
500mm	10.150.012	1	
		10	





Varnish Roller Nylon (Standard Quality)

Varnish Roller Nylon (Premium Quality)

Pile Height 18 mm,

Pile Height 14 mm red/red thread, for topcoat application on smooth surfaces Core Ø 48 mm

Width		
250 mm	10.101.014	10
		100

Core Ø 48mm		
width 180 mm	10.118.018	
250 mm	10.100.018	'
400 mm	10.140.018	

for topcoat application on rough and sanded surfaces

180 mm	10.118.018	10
		100
250 mm	10.100.018	10
		100
400 mm	10.140.018	1
		10
500 mm	10.150.018	1
		10

ces

width		
180 mm	10.218.013	10
		100
250 mm	10.200.013	10
		100

Varnish Roller Gold Stripe – Polyamide
Pile Height 18 mm
not padded; for sanded and smooth surfaces
generially quitable for water based resins

Core Ø 48 mm

width		
180 mm	10.218.018	10
		100
250 mm	10.200.018	10
		100

























Item-No. Package/Piece Piece/Pair

Varnish Roller Gold Stripe - Polyamide

Pile Height 18 mm padded 4 mm for rough and uneven surfaces especially suitable for water based resins Core Ø 48 mm

width

180 mm 10.218.002 10 100 250 mm 10.200.002 10 100

Varnish Roller "Professional"

Pile Height 21 mm soft padded 8mm, Polyamide for rough surfaces (e.g. Brick facade) Core Ø 48 mm

width

10.218.021 180 mm 10 250 mm 10.200.021 10

Facade Roller "Jumbo"

Pile Height 21 mm soft padded 12mm, Polyamide for rough surfaces (e.g. Brick facade) Core Ø 48 mm

width

180 mm 10.288.021 10 250 mm 10.285.021 1 10

Polyester Roller

Pile Height 18 mm not padded, for low viscosity materials Core Ø 48 mm

width

180 mm 10.818.018 10 100 250 mm 10.825.018 10 100

Polyester Roller

Pile Height 18 mm padded, for low viscosity materials Core Ø 48 mm

width

180 mm 10.848.018 10 100 250 mm 10.845.018 10 100





			€
Item	Item-No.	Package/Piece	Piece/Pair

Varnish Paint Roller Mohair


Pile Height 5 mm, Core Ø 48 mm

width

10.318.001 180 mm 10 100 250 mm 10.300.001 10 100



Pile Height 5 mm, (economical alternative to Mohair), Core Ø 48 mm



Lambwool Roller Pile Height 20 mm Core Ø 48 mm

> width 180 mm 250 mm

10.518.001 10.525.001

10

10

10



Varnish Roller "Microfaser"

Pile Height 5 mm, Core Ø 48 mm

width

250 mm 10.625.005 100

Varnish Roller "Microfaser" Pile Height 8 mm, Core Ø 48 mm

width

250 mm 10.625.008 10 100 500 mm 10.650.008 10

Varnish Roller "Microfaser"

Pile Height 11 mm, Core Ø 48 mm

width

250 mm 10.625.011 10 100 500 mm 10.650.011 1 10







width

100 mm

15.610.000









				. €
	Radiator Roller Polyamid	Item-No.	Package/Piece	Piece/Pair
	Pile Height 13 mm, Core Ø		iyaiiiiu e	
	width			
	100 mm	15.310.013	10 100	
	150 mm	15.315.013	10 100	
	Midiroller		100	
	Core Ø 30 mm			
	width 120 mm	15.312.013	10	
	120 11111	10.012.010	100	
	Textured Radiator Roller Core Ø 35 mm			
	width 110 mm	15.600.002	10	
The same of the sa			100	
	Textured Radiator Roller			
	Superfine 10cm, both ends with groove to av	oid rollormarke a	nd application eter	ne.
	6 mm Peahole	ioiu ioileimaiks a	nu application step	JS
	width			
	110 mm	15.601.110	10 100	
	Textured Radiator Roller			
	6 mm Peahole			
	width			
	110 mm	15.600.003	10 100	
0100				
	Textured Radiator Roller			
	Fine, Core Ø 35 mm			
	width 110 mm	15.600.001	10	
	Superfine, Core Ø 35 mm		100	
	width 110 mm, straight	15.601.101	10	
			100	
	110 mm, one side round		10 100	
	110 mm, bilaterally round	I 15.601.101 R	10 100	
	Radiator Roller Mohair			
	Pile Height 5 mm, Core Ø 1	7 mm		
	width	15 410 005	40	
	100 mm	15.410.005	10 100	
	150 mm	15.415.005	10 100	



			€
Item	Item-No.	Package/Piece	Piece/Pair
Radiator Roller Velour Pile Height 5 mm, Core Ø width 100 mm	17 mm 15.510.005 15.515.005	10 100 10 100	
Radiator Roller "Microfa Pile Height 6 mm, Core Ø width 100 mm Pile Height 8 mm, Core Ø 100 mm 150 mm	17 mm 15.610.006	10 100 10 10 10 10	
Pipe Roller Ø=60mm Complete Replace Ø=100mm Complete Replace	15.700.060 15.710.060 15.700.100 15.710.100	1 3 1 3	
Roller Handle Economy size between 32-50 cm 320-500 mm	15.900.040	1	
Roller Handle Width for 2 standard 25 cr 500 mm	n Roller 15.900.250	1	
Roller Handle size between 40-60 cm 400-600 mm	15.900.050	1	



				€
	Item	Item-No.	Package/Piece	Piece/Pair
	Roller Handle with hollow plastic g width 120 mm	rip, Ø 8 mm 15.900.812	5	
			20	
	180 mm	15.900.818	5 20	
	250 mm	15.900.825	5 20	
	Roller Handle for sr Handle with hollow p width			
	28 cm	15.910.028	5	
	40 cm	15.910.040	20 5	
	55 cm		20	
	oo ciii	15.910.055	5 20	
	Roller Handle 5 cm with hollow plastic of	rip; 5 cm Roller Handl	e· M6mm	
		rip, o om nonor nanar	o, 9 0mm	
	Length 20 cm	15.910.005	5 10	
\bigcap	Grid			
	Plastic 27 x 29 cm	10.900.290	10	
	Metall 26 x 30 cm	10.900.300	10	
	Paint Tray			
	100% PP, solvent res			
	15 x 29 cm 31 x 35 cm	10.910.329 10.910.350	10 10	
	31 x 47 cm	10.910.470	10	
	Paint Bucket 12 Liter			
	100% PP, solvent res 38 x 26 x 20 cm	sistant, stackable 10.920.012	5	



	Item	Item-No.	Package/Piece	€ Piece/Pair
	Belgium Floor Trowel stainless steel sheet thickness 1,0 mm 30 cm, width 110	20.903.030	1	
	45 cm, width 110	20.903.050	1	
	Swedish floor trowel carbon steel, short bar for length 50cm width front/back 75/120 sheet thickness 0,7 mm		1	
	Screet Trowel open hand	le, stainless steel		
	length 50 cm, width front/back 75/110 sheet thickness 0,7 mm sheet thickness 1,1 mm length 60 cm width front/back 75/110 sheet thickness 1 mm		1 1	
	Careed Travel aloned has	ndla		
	screed Trowel closed had stainless steel length 50 cm width front/back 85/110 sheet thickness 0,7 mm width front/back 75/110 sheet thickness 1 mm ength 60 cm width front/back 85/110 sheet thickness 0,7 mm width front/back 75/110 sheet thickness 1 mm Screet Trowel closed had carbon steel length 50 cm width front/back 85/110 sheet thickness 0,7 mm width front/back 85/110 sheet thickness 0,7 mm width front/back 75/110 sheet thickness 1,1 mm length 60 cm width front/back 80/120 sheet thickness 0,7 mm width front/back 75/110 sheet thickness 1 mm	20.900.007 20.900.010 20.900.067 20.900.061 adle	1 1 1 1	
	Floor Trowel stainless steel, both end ro sheet thickness 0,7mm 29,5 x 8 cm	unded 20.903.041	1	
	sheet thickness 1,0mm			
	42,5 x 12,5 cm	20.903.042	1	



Item	Item-No.	Package/Piece	Piece/Pair
Swiss Trowel 48 x 13 cm, stainless stee sheet thickness 0,7 mm Toothed Swiss Trowel 48 x 13 cm, stainless stee sheet thickness 0,7 mm 6 mm acute toothing 3 mm rectangle toothing Other teeth and stainless	20.101.004 20.101.604 20.101.314	1 1	
Floor Spatula width 30 cm 40 cm 50 cm	20.904.030 20.904.040 20.904.050	1 1 1	
Smoothing Trowel 13 x 28 cm carbon steel stainless steel	20.100.001 20.101.001	3 30 3 30	
Finishing Trowel Long To Sheet thickness 0,7 mm, carbon steel stainless steel		1	
Finishing Trowel Long To Sheet thickness 0,7 mm, carbon steel stainless steel		1	
American Trowel big handle and long bar, s' Sheet thickness 0,7 mm Dimensions: 13 x 28 cm 11 x 26,7 cm	20.101.002 20.101.003	1 1	
Special Trowel for Resin stainless steel, 7,5 x 35 cm sheet thickness 0,7 mm sheet thickness 1,0 mm	n 20.101.005	1 1	







Item	Item-No.	Package/Piece	Piece/Pair
Plasterer Trowel stainless steel length 120 mm length 140 mm carbon steel length 140 mm	20.600.120 20.600.140 20.610.140	3 3 3	
Stuccoists Spatula stainless steel width 4 cm width 5 cm width 6 cm width 8 cm width 10 cm	20.800.004 20.800.005 20.800.006 20.800.008 20.800.010	3 10 3 10 3 10 3 10 3 10	
Cat's Tongue Trowel stainless steel length 140 mm	20.700.140	3	
Tongue Trowel stainless steel length 160 mm	20.710.160	3	
Edge Trowel stainless steel for inner corners for outer corners	20.851.080 20.852.080	3 3	
Trowel with clamps stainless steel, width 28 for right hand for left hand	20.128.002 20.128.003	1 1	
Adhesive Spreader Alufitted with clamps to hole width 280 mm Tooth blades page 31		othed blades 1	







Item-No. Package/Piece Piece/Pair

Concave and Triangle Bevelled Trowel without edge

made of special stainless steel, blade thickness 2 mm, non flexible r = 40 mm, Socket height 60 mm, 45 degrees both sides

> 20.302.045 1



Triangle Trowel

both ends bevelled, tigh 30mm, stainless steel

20.303.030 1

both ends bevelled, tigh 40mm, stainless steel

20.303.040 1



Round Trowel 30mm

stainless steel, 1 mm blade thickness, 170 mm length

r =30 mm 20.304.030 1 r =50 mm 20.304.050



Profile Trowel

stainless steel, 65 mm width, 250 mm length

r = 30 mm 20.304.031 r = 50 mm 20.304.051



Profile Trowel 50mm obliquely

stainless steel, 65 mm width, 250 mm length, both ends bevelled

r = 30 mm 20.304.032 r = 50 mm 20.304.052



Concave Bevelled Trowel with edge

made of special stainless steel, blade thickness 2 mm, non flexible, with 0,2" edge

r = 40 mm, Socket heigh 60 mm, 45° both sides

20.301.045 1



Float with Latex Plate

280 x 140 mm

20.150.090 3

Replacement plate

20.150.091 3



	Item	Item-No.	Package/Piece	Piece/Pair
	Float with Cellur Caotcho	ouc Plate 20.150.050	3	
	Replacement plate	20.150.051	3	
	"HYDRO" Sponge Float 280 x 140 x 40 mm			
	normal sceened	20.150.060 20.151.050	3 3	
	Replacement plate Hydro normal sceened	20.150.061 20.151.051	3 3	
	"Hydro" Sponge Float wi 280 x 140 x 40 mm	th Velcro		
	sceened	20.151.060	3	
	Replacement plate sceened	20.151.061	3	
	Float with Sponge Rubbe thickness 10mm, Dimension		3	
	Replacement plate thick rough	ness 10 mm 20.150.072	3	
Carried State of Stat	Float with Sponge Rubbe thickness 20mm, Dimension		3	
	Replacement plate thick fine rough	ness 20 mm 20.150.082F 20.150.082G	3 3	
	Viscose Sponge			
	150 x 110 x 35 mm Hydro Sponge	21.150.035	5	
	165 x 110 x 70 mm	21.160.070	3	
	Sponge for Epoxi			
	hard 150 x 100 x 50 mm	20.450.001	3	
	extra hard 150 x 100 x 50 mm	20.450.002	3	
	Combi Sponge 160 x 100 x 60 mm	20.450.005	3	





white width 550 mm

red

750 mm

width 550 mm


25.004.055

25.003.055

25.003.075

3 10

3 10














			01
Item	Item-No.	Package/Piece	€ Piece/Pair
Tooth Blades Dimensions in mm:			
Width 280 mm; H=Toothhei () = Number pf pages serra		S=Topwidth	
toothing S1 H=9,2 L=10,0 S=0,2 (1)	20.000.S1	10	
toothing S2 H=7,7 L=8,2 S=0,2 (2)	20.000.S2	10	
toothing S3 H=5,2 L=6,2 S=0,2 (2)	20.000.S3	10	
toothing S4 H=5,1 L=10,3 S=0,2 (2)	20.000.S4	10	
toothing S5 H=4,2 L=5,7 S=0,2 (2)	20.000.S5	10	
toothing S6 H=3,4 L=4,2 S=0,2 (2)	20.000.S6	10	
toothing S8 H=1,8 L=2,5 S=0,2 (2)	20.000. S 8	10	
toothing S9 H=4,4 L=2,8 S=0,2 (2)	20.000.S9	10	
toothing A2 H=1,5 L=1,8 S=1,2 (2)	20.000.A2	10	
toothing A3 H=1,5 L=1,5 S=0,5 (2)	20.000.A3	10	
toothing R1 H=3,0 L=4,0 S=1,6 (2)	20.000.R1	10	
toothing R2 H=5,0 L=4,0 S=2,0 (2)	20.000.R2	10	
toothing R3 H=3,0 L=3,0 S=3,0 (2)	20.000.R3	10	
toothing R4 H=4,0 L=4,0 S=4,0 (2)	20.000.R4	10	
toothing R5 H=6,0 L=6,0 S=6,0 (2)	20.000.R5	10	
toothing R6 H=8,0 L=8,0 S=8,0 (2)	20.000.R6	10	
toothing R7 H=10,0 L=10,0 S=10,0 (2)	20.000.R7	10	
toothing RS4 H=5,5 L=6,5/1,9 S=0,2	20.000.RS4	10	
Illustration 1:1			







Item Item-No. Package/Piece Piece/Pair

Rollerbox

made of solvent resistant plastic,

for storage in solvent of used spike roller up to 25cm

19.310.025 1



made of solvent resistant plastic, fits on standard roller handle

Spike length 11 mm

width	
7 cm	

7 cm	19.012.007	1
12 cm	19.012.012	1
18 cm	19.012.018	1
25 cm	19.012.025	1
50 cm	19.012.050	1
70 cm	19.012.070	1

Spike length 21 mm

width	
wiuii	

19.021.007	1
19.021.012	1
19.021.018	1
19.021.025	1
19.021.050	1
19.021.070	1
	19.021.012 19.021.018 19.021.025 19.021.050

Spike length 35 mm

width

19.035.025	1
19.035.050	1
19.035.070	1
	19.035.050

Spike Roller Metal

Spike ø 0,4 mm, length approx.13 mm

width

25 cm	19.100.025	1
50 cm	19.100.050	1

with reduced metal spikes, spike length ca. 18 mm, therefore better cleaning properties

width


25 cm	19.101.025	1
50 cm	19.101.050	1


Loop Roller

very much suitable to smoothen thin coatings

wi		

19.200.018	1
19.200.025	1
19.200.050	1
	19.200.025





The Resident House of the







Item Item-No. Package/Piece Piece/Pair

Copper Tape

self adhesive, conductive acrylic adhesive

width 9 mm, length 33m, thickness 0,06mm 48.530.010



Floor Grounding Kit

with 1m self adhesive copper tape

48.000.010



Warning Sign Flooring Works

card board display

99.366.035



Tape Brush

to press the tape onto the substrate

Dimension 150 x 60 mm

30.700.150



Item Item-No. Package/Piece Piece/Pair

Professionell Silver Masking Tape (50 m)

consists of a heavy duty, waterproof and plastic coated fabric, coated with a natural rubber glue, resistant against water, oil, mechanical damage and many chemical influences, length $50\ m$

Sta			-1 (\	124
STA	nn	ar	пı	ша	IIITV

width 38 mm	70.701.038	4
		32
width 50 mm	70.701.050	4
		24

Premium Qualität high UV-resistant

consists of a heavy duty, waterproof and plastic coated fabric, coated with a natural rubber glue, resistant against water, oil, mechanical damage and many chemical influences, length 50m

width 38 mm	70.702.038	30
width 50 mm	70.702.050	24



Wire-Cloth Tape (50 m)

consists of a heavy duty, tear- and waterproof, PE-coated cloth, coated with a special natural rubber glue, on one edge fixed a thin wire to enable a sharp cutting of the cured coating, length 50 m

width 50 mm 70.799.025 1



Universal Cloth Tape (25 m)

tear- and waterproof, PE-coated cloth, coated with a special natural rubber glue of high UV stability and tackiness, length 25 m

width 38 mm	70.700.038	4
		30
width 50 mm	70.700.050	4
		24
Top Quality (50 m)		
width 38 mm	70.703.038	4
		24
width 50 mm	70.703.050	4
		18



Masking Tape Indoor (50 m)

low budget smooth tape with good adhesive performance, impregnated, tear proof crepe paper, coated with a soft synthetic rubber glue (solvent free) use only for short time, length $50\ m$

14	ris	tt	h
W	,,,	u	"

38 mm	70.100.038	24
50 mm	70.100.050	24



Professionell Masking Tape Indoor (50 m)

consists of an impregnated, tear proof and tough crepe paper, coated with a soft modiefied naturalrubber glue of good adhesive strength and ageing resistancet, length 50 m

width		
19 mm	70.110.019	48
25 mm	70.110.025	36
30 mm	70.110.030	30
38 mm	70.110.038	24
50 mm	70.110.050	24









Package/Piece

Piece/Pair

Professionell Masking Tape Outdoor (50 m)

a high-quality crepe tape, coated with a special acrylic glue. The tape is resistant to moisture, heat (80°C) and uv resistent, length 50m


width		
19 mm	70.120.019	48
25 mm	70.120.025	36
38 mm	70.120.038	24
50 mm	70.120.050	24



consists a heavy duty and flexible LD-PVC-foil, coated with a natural rubber glue; it is waterproof and resistant against low temperature, moister, oils, bases, acids and many other chemicals; smooth, high strechable plastic tape, yellow, length 33m

color: yellow		
width 30 mm	70.200.030	4
		60
width 50 mm	70.200.050	4
		36
color: white		
width 30 mm	70.210.030	4
		60
width 50 mm	70.210.050	4
		36





white, glue on both sides on backside with a non glue edge, length 25 \mbox{m}

width 25 mm	70.900.025	8
		48
width 35 mm	70.900.035	8
		48



Double Masking Tape white, glue on both sides, suitable to bond cover sheets, length 50 m

width 25 mm	70.912.025	4
		12
width 50 mm	70.912.050	1
		6





cover sheet made of PE with blue cloth reinforced masking tape

length 20 m width		
550 mm	70.920.055	5
		30
1100 mm	70.920.110	5
		30
1400 mm	70.920.140	4
		30
1800 mm	70.920.180	4
		30
length 17 m width		
2700 mm	70.920.270	4
		30







Bond+Cover K Bond+Cover K cover	sheet made of PE with paper	masking tape, only indoor
length 33 m width		
300 mm	70.921.030	5
		60
550 mm	70.921.055	5
		60
1100mm	70.921.110	4
		30
1800 mm	70.921.180	4
		30
length 17 m width		
2600 mm	70.921.260	4
		30

Item-No.

€

Piece/Pair

Package/Piece



Bond+Cover P (25 m)

cover sheet made of paper with paper masking tape

width

180 mm 70.922.180 10 60



Covering Felt (50 m)

one side covered with anti slip film, length 50 m

width 1 m 40.810.150 1



Multi layer paper role (approx. 60 m)

both sides polypropylen coated, recomended to protect floors, length 60 m

width ca.

125 cm 40.820.120



Covering Sheet (50 m)

suitable for mixing base, length 50 m thickness 0,1mm, width 2m

40.800.150 1

3



Covering Sheet (100 m)

thickness 0,1mm, width 2m, length 100m

width

2000 mm 40.807.200 2







	Item	Item-No.	Package/Piece	€ Piece/Pair
	Arenga Broom			
	30 cm	30.030.030	3	
	50 cm	30.030.050	10 3	
A CONTRACTOR OF THE PARTY OF TH	60 cm	30.030.060	10 3	
CAMBOO SOLUTION	00 0	0010001000	10	
	Hand Brush (Arenga/Ela	ston)		
Management	width			
	28 cm	30.001.028	3 10	
A COLOR DE LA COLO				
	Industiral Hand Brush (d	coconut)		
	width			
	28 cm	30.001.029	3 10	
	long handle 45 cm	30.045.028	3	
	45 Cm	30.043.020	10	
	Hand Broom			
	width			
	30 cm	30.001.030	3 10	
	Dust Pan Metal dust pan with wood	len handle		
	width			
	22 cm	30.002.022	1 10	
	Wire Broom			
-	wooden frame with stick	hole		
	width 30 cm	30.100.030	3	
Market A. C.	30 GIII	30.100.030	3	
Add to the second				
	Wire Scrubbing Brush	hala		
	wooden frame with stick	note		
And a delibilities of the state	width 22 cm	30.101.022	3	
4 1 / 1 / 1				
	Wire Hand Brush wooden frame, 4 wire rov	vs		
	width			
All Marians	30 cm	30.101.030	3	



	Item	Item-No.	Package/Piece	Piece/Pair
	Universal Wire Brush Brass with plastic handle 1 row Wire brush, Thickness 0,3 2 row 4 row Wire brush, Thickness 0,3 3 row 4 row Wire brush, Thickness 0,3 2 row 4 row Scaling Spatula	30.102.002 30.102.004 81mm, straight, s 30.102.013 30.102.014	1	
E TOTAL STATE OF THE PARTY OF T	width 5 cm 7 cm	30.202.005 30.202.007	1 1	
	Floor Scraper Scraper and Stick width 30 cm Replacement Blade Stick for Floor Scraper	30.200.030 30.201.030 30.201.000	1 1 1	
	Scraper extra heavy steel blade 8 cm	30.200.008	1 3	
	Spatula strong, heavy steel blade, width 7 cm	approx. 30 cm lo	ong 1	
	Paint Scraper with soft handle width 50 mm Replacement Blades for width 50 mm Replacement Blades sp width 50 mm	30.213.051	1 10 213.050 3	
	Paint Scraper with soft handle, and butt width 64 mm Replacement Blades for width 64 mm	30.213.064	ressure 1 3	



			€
Item	Item-No. Pa	ckage/Piece	Piece/Pair
Shovel round shovel, type Frankfur Shovelstems (DIN 20151) 130 mm made from ash	30.300.030	3 10	
made from asn	30.300.038	3	
Shovel Flat	30.300.031	3 10	
Shovelstems (DIN 20151) 130 mm made from ash	30.300.038	3	
Replacement Stick			
Ø 28 mm (for 30.300.030) 1,50 m 2 m	30.300.150 30.300.228	5 5	
Ø 24 mm 1,40 m 1,50 m	30.324.140 30.324.150	5 5	
Telescopic Stick			
 Steel 60 cm Alu	30.300.060	3	
2 x 150 cm with clip 3 x 100 cm with thread	30.300.300 30.310.310	3 3	
Hammer Ash stick			
1 Kg	30.800.001	1	
Cross Peen Hammer with ash handle and impact	protection, acc. DIN	1041	
500 g	30.800.005	1	
Pointed Chisel made from Crome-Vanadiu			
L 200 Ø 14 (mm) L 200 Ø 16 (mm) L 250 Ø 16 (mm)	30.820.014 30.820.016 30.825.016	1 1 1	
Maison's Chisel made from Chrome-Vanadi	mu		
L 200 Ø 14 (mm) L 200 Ø 16 (mm) L 250 Ø 16 (mm)	30.920.014 30.920.016 30.925.016	1 1 1	





€ Item Item-No. Package/Piece Piece/Pair **Side Cutting Nipper** length 200mm, head polished, handle dip-paint isolated, Made in Germany 30.865.200 **Stripping Plier** length 150mm, handle dip-paint isolated, Made in Germany 30.868.150 1 Stripping Knife with hooked blade 30.945.100 1 Automatik wire stripper for wires from 0,2-4mm 30.940.100 1 **VDE Voltage Tester** 220-250Volt, length 190mm 30.930.190 1 **VDE Voltage Tester** length 100 mm 30.935.100 **VDE Screwdriver Set 6 pc** black color blade, CV-Blade, 3 component handle Slot: Blade length: 80 mm Blade: 3,0 100 mm Blade: 4,0 125 mm Blade: 5,5 150 mm Blade: 6,5 Cross: Blade length 80 mm Blade: PH1 100 mm Blade: PH2

VDE Voltage Tester

30.880.007

Piece/Pair



Item-No.



Screwdriver Set 6 pc

black color blade, CV-Blade, 3 component handle

Slot:

Item

Blade length

80 mm Blade: 3,0

100 mm Blade: 4,0

125 mm Blade: 5,5

150 mm Blade: 6,5

Cross:

Blade PH1 and PH2

30.870.006

1

Package/Piece



Screwdriver Set 4 pc

CV-Blade, soft handle

Slot:

Blade length

100 mm Blade: 5,0


150 mm Blade: 6,0

Cross:

Blade length

100 mm Blade: PH1 150 mm Blade: PH2

30.878.004




ltem ltem-No. Package/Piece Piece/Pair

HSS Drill Set Ø 1,0-13 mm

25 pc; profile grounded; for steel and wood

30.878.013



25 pc; rolled; for steel and wood

30.879.013



HM Drill Set Ø 3,0-10,0 mm

for stone and concrete; 8 pc

30.880.010 1




Bit Set 7 pc

Top Quality, Made in Germany

1x magnetic holder, 1x PH1, 1x PH2, 1x PZ1, 1x PZ2, 1x 0,8x5,5 1x 12x6,5

30.880.017 1



F-Clamp span width 30cm

throat depth 120mm

30.881.030 1



Tipped Core Bit

Ø 66mm	30.875.060	1
Ø 80mm	30.875.080	1

Item

€ Item-No. Package/Piece Piece/Pair

Craftsman Bag

made from polytex; 420x150x250mm

200.42.150.250





Craftsman Bag with tools

- 1x Comb pliers
- 1x Telephone pliers
- 1x Diagonal cutting pliers

electricion screwdriver - 6pieces acc. VDE proof; up 1000Volt; testet with 10000V , from chrom-vanadium-steel 58 CrV4, Cross scrfew driver from chrom-vanadium-steel 61 SiCrV5, ergonomic 2 comp. handle;

size: 6,5x150 5,5x124 4x100 2,5x75

Cross Screwdriver PH1 and PH2

- 1 Jokari cable stripping knive
- 1 Jokari wire stripper
- 1 voltage tester, Made in Germany VDE proofed 125-250V
- 1 Universal saw
- 1 Electrician chissel 10x8x250mm Made in Germany
- 1 cross peen hammer
- 1 painters spatula 40mm wooden handle
- 1 plastering bath
- 1 carpenter pencil
- 1 balance 30cm
- 1 folding ruler

200.42.150.500



Scatter Tub

made of plastic, incl. 1 carrying strap

Size 20 I for approx. 25 kg sand

30.500.010

Replacement Straps

30.500.015



Scoop

plastic

Size 0,7 I 30.401.007 1
Size 1,1 I 30.401.011 1







€ Package/Piece Piece/Pair

1

1

1

1



Construction Lamp 108 Watt

suitable for outdoor use

2 sockets (IP 54) for connecting additional electrical appliances up to a maximum of 2000 watt, Energy-saving fluorescent lamps, Heavy rubber cable (5 m), Aluminium reflector, No risk of burning, Shock-proof, Oil-resistant case, Suitable for outdoor application, Cold, non-glare light, Progressively adjustable pedestal

Item-No.

Dimension: L: 550 mm W: 285 mm H: 115 mm

99.454.108



Halogen Floodlight 1500 Watt

incl. 5m rubber-sheathed cable, suitable for outdoor use

99.400.150 1



Halogen Floodlight 1000 Watt

incl. 5m rubber-sheathed cable The floodlights are made with a plasticcoated aluminium diecast housing and frame. They are equipped with an aluminium reflector, hardened safety front glass, silicone sealing, lamp socket R7S and a junction box with grounding terminal. All models are suitable for outdoor areas.

Dimension: L: 340 mm W: 405 mm H: 400 mm

99.410.150



Halogen Floodlight 500 Watt

incl. 1,5m rubber-sheathed cable The floodlights are made with a plasticcoated aluminium diecast housing and frame. They are equipped with an aluminium reflector, hardened safety front glass, silicone sealing, lamp socket R7S and a junction box with grounding terminal. All models are suitable for outdoor areas.

Dimension: L: 195 mm W: 155 mm H: 329 mm

99.420.500



Halogen Floodlight 500 Watt with Tripod

incl. 5m rubber cable. Mobile tripod (1,8 m)

The floodlights are made with a plastic-coated aluminium diecast housing and frame. They are equipped with an aluminium reflector, hardened safety front glass, silicone sealing, lamp socket R7S and a junction box with grounding terminal. All models are suitable for outdoor areas.

Dimension: L: 185 mm W: 155 mm H: 1800 mm

99.430.500



Item

€ Piece/Pair

Telescopic Tripod

Telescopic tripod for construction lamps and halogen floodlights continuously adjustable 100-250cm

Item-No.

99.444.250

Package/Piece

1





Twin Cross Bar

for installation of 2 halogen floodlights or construction lamps on the tripods (without flood ligths)

99.444.002

Screw Set

 $10\ pcs.$ srew-set for the installation of 1 construction lamp on the suitable crossbar

99.444.010



Cabel Drum 40 m

Splashpater protectet, protection type IPX4
Plastic cable reels with H07RN F3G1,5 according to BGI 608
Design in plastic sheet, Ergonomic handle, Plug parking position, Rotation stop switch, Steel reel connected to earth, Can be used in standing or flat position, Extremely stable thanks to low centre of gravity

31.500.040



Deep Hole Marker

Marking and writing tool with permanent ink, Can be washed off of smooth surfaces with alcohol

30.995.003



Water Balance

width

60 cm 40.220.060 1 80 cm 40.220.080 1



Wax Mark-Chalks

yellow 40.250.001

Carpenter Pencil

Top Quality

25 cm 40.230.025 5





tem	Item-No.	Package/Piece	Piece/Pair
Marking Rope			
Metal Case			
	40.260.001	1	
Pigment Powder			



for marking rope			
blue 250 gr 500 gr	40.260.250 40.260.500	1 1	
red 250 gr 500 gr	40.260.251 40.260.501	1 1	



Barrier Tape red/white

length 500 m

width 80 mm 40.400.580 1



Waste Bag

120 litre, 70 x110cm, top quality, extra strong, approx 80µm, 10 bags per role, Price per role

40.400.120 1 blue

Waste Bag

120 Liter, 70 x 110 cm, approx. 80 μm, LDPE 15 bags per role, Price per role

transparent 40.410.120 1



Measure Cap solvent resistant

3 L

5 L

50 ml 40.600.050 10 100 ml 40.600.100 10 250 ml 40.600.250 1 6 500 ml 40.600.500 1 6 1 L 40.600.001 1 6 40.600.002 2 L 1 2

40.600.003

40.600.005

1 2

1 2





€ Item-No. Package/Piece Piece/Pair

Line Marking Applicator

Line width

100 mm 45.000.100



Pistol for aerosol line marking paint

45.000.001

1



Aerosol Line Marking Paint durabel, trafficable Epoxyd Paint 8 standard and 2 fluorescent paints

 $750\ ml;$ gives a approx. $100\ m$ long and $5\ cm$ width sharp and clear line

white (RAL 9016)	45.010.001	1
		6
yellow (RAL 1023)	45.010.002	1
		6
red (RAL3020)	45.010.003	1
		6
blue (RAL 5017)	45.010.004	1
		6
green (RAL 6024)	45.010.005	1
		6
orange (RAL 2009)	45.010.006	1
		6
black (RAL 9017)	45.010.007	1
		6
light grey (RAL 7045)	45.010.008	1
		6
rose fluorescent	45.020.001	1
		6
yellow fluorescent	45.020.002	1
		6






Item	Item-No.	Package/Piece	Piece/Pair
Template			
Template 150 mm			
T I I	45.090.001	1	
Template 300 mm	45.090.003	1	
Handicap template	4= 000 004	_	
66,1 x 55,9 cm	45.090.004	1	



Line Marking Tape width 50 mm, length 33 m white yellow red blue green black/white stripes red/white stripes width 75 mm, length 33 m white yellow red blue

2 2 45.150.001 45.150.002 2 45.150.003 2 45.150.004 2 45.150.005 45.150.010 2 2 45.150.011 45.175.001 2 45.175.002 2 45.175.003 2 45.175.004 2 2 green 45.175.005 black/white stripes 45.175.010 2 2 red/white stripes 45.175.011



Application Tool for Line Marking Tape

Professionel application tool for line marking tapes for 50 und 75 mm width tapes incl. yellow or white tape

> 45.100.001 1






Item	Item-No.	Package/Piece	€ Piece/Pair
Hard Metal Disk double sided			
Ø 375 granulation coarse granulation medium	52.H37.16 52.H37.24	1 1	
Ø 400 granulation coarse	52.H40.16	1	
granulation medium granulation fine	52.H40.24 52.H40.36	1	
Ø 430 granulation coarse	52.H43.16	1	
granulation medium	52.H43.24	1	

Double Sided Sanding Diskwith silicium carbid, coarse granulation open sanded,
fine granulation dens sanded
Disk Ø 20 and 30 cm on request

Disk Ø 37,5 cm		
Granulation 12	52.375.12	10
Granulation 16	52.375.16	10
Granulation 24	52.375.24	10
Granulation 36/40	52.375.40	10
Granulation 60	52.375.60	10
Granulation 80	52.375.80	10
Granulation 100/120	52.375.120	10
Disk Ø 40 cm		
Granulation 12	52.400.12	10
Granulation 16	52.400.16	10
Granulation 24	52.400.24	10
Granulation 36/40	52.400.40	10
Granulation 60	52.400.60	10
Granulation 80	52.400.80	10
Granulation 100/120	52.400.120	10
Disk Ø 43 cm		
Granulation 12	52.430.12	10
Granulation 16	52.430.16	10
Granulation 24	52.430.24	10
Granulation 36/40	52.430.40	10
Granulation 60	52.430.60	10
Granulation 80	52.430.80	10
Granulation 100/120	52.430.100	10
Diel G FO em		
Disk Ø 50 cm	E0 E00 4C	10
Granulation 16 Granulation 24	52.500.16	10
Granulation 24 Granulation 40	52.500.24 52.500.40	10
Granulation 40	52.500.40 52.500.60	10 10
Granulation 80	52.500.80 52.500.80	10
Granulation 100/120	52.500.60 52.500.120	10
uranulation 100/120	J2.JUU.12U	10







ltem	Item-No.	Package/Piece	€ Piece/Pair
Grinding Float made from hard metal			
Size 12x22cm Granulation 14 Granulation 24	52.120.014 52.120.024	1 1	



Backside with inside thread M14			
Size 110 x 90 x 22	mm		
Korn 16/24	54.110.916	3	
Korn 24/36	54.110.924	3	
with thread			
Korn 16/24	54.120.916	3	
Korn 24/36	54.120.924	3	



ZEC - Grinding Disks with holes, for quick and easy dust removal,

Grinding Pot for Stone

with holes, for quick and easy dust removal sanded with silicium carbid





Flexible Grinding Disc

with corundum bonded in systhetic resin, flat


Ø 115 mm		
Granulation 16	53.115.016	25
Granulation 24	53.115.024	25
Granulation 40	53.115.040	25
Granulation 60	53.115.060	25
Granulation 80	53.115.080	25
Ø 125 mm		
Granulation 16	53.125.016	25
Granulation 24	53.125.024	25
Granulation 40	53.125.040	25
Granulation 60	53.125.060	25
Granulation 80	53.125.080	25
Ø 178 mm		
Granulation 16	53.178.016	25
Granulation 24	53.178.024	25
Granulation 40	53.178.040	25
Granulation 60	53.178.060	25
Granulation 80	53.178.080	25











Hand Grinder with express adjusters

with express adjusters

80 x 240 mm 56.200.001 1



Sanding Drum Grain

115mmx50m, E-paper (220-270g), dense coated, aluminium oxide, resin bond

Granulation:

60	53.415.060	1
80	53.415.080	1
120	53.415.120	1
180	53.415.180	1
240	53.415.240	1

Weitere Granulationen auf Anfrage.



Sanding Drum Grain

115mmx50m, C-paper (110-135g), semi open coated, aluminium oxide, resin bond $\,$

Granulation:

60	53.413.060	1
80	53.413.080	1
120	53.413.120	1
180	53.413.180	1
240	53.413.240	1



Sanding Paper Grain

Dimension: 230x280mm flexible C-Latex paper 110-135g, semi open coated, aluminium oxide, resin bond

Granulation:

60	53.400.060	5
80	53.400.080	5
120	53.400.120	5



Stick Fix Sanding Disk

 \emptyset 115 mm perforated with 8+1 holes, semi open coated, aluminium oxide, resin bond

Granulation:

40	53.416.040	50
60	53.416.060	50
80	53.416.080	50
120	53.416.120	50



Stick Fix Sanding Disk

 \emptyset 115 mm perforated with 8+1 holes, semi open coated, for varnish, stearat bond

Granulation:

180	53.516.180	
240	53.550.240	100

















Item-No. Package/Piece Piece/Pair

€

Stick Fix Sanding Disk

Ø 125 mm perforated with 8+1 holes, semi open coated, aluminium oxide, resin bond

Granulation:

40	53.425.040	50
60	53.425.060	50
80	53.425.080	50
120	53.425.120	50

Stick Fix Sanding Disk

Ø 125 mm perforated with 8+1 holes, semi open coated, for varnish, stearat bond

Granulation:

180	53.525.180	100
240	53.525.240	100

Stick Fix Sanding Disk

Ø 150 mm perforated with 8+1 holes, semi open coated, for varnish, stearat bond

Granulation:

40	53.450.040	10
60	53.450.060	10
80	53.450.080	10
120	53.450.120	10

Self adhesive Pads for Delta Sander

Dimension: 93 x 93 x 93 mm 6L

- Basematerial: E-Paper 220 to 270 g/m²

- Bonding: Resin - Grain type: Corundum Price / Package with 50 pc

Granulation:

40	53.347.040	1
60	53.347.060	1
80	53.347.080	1

Self adhesive Pads for Delta Sander

(Makita, Bosch, Metabo, Black+Decker) Dimension: 88 x 93 mm 6L

- E-Paper 220 to 270 g/m^2

- Bonding: Resin

- Grain type: Corundum

Price / Package with 50 pc

Granulation:

40	53.390.040	1
60	53.390.060	1
80	53.390.080	1

Sanding Spone

for wet and dry grinding

Dimension 100 x 70 x 27 mm

Granulation

80	56.200.080	2
100	56.200.100	2
180	56,200,180	2






100x235

56.340.010


1







Item	Item-No.	Package/Piece	€ Piece/Pair
Handpad (Super Pad)			
115 x 250			
black	56.340.001	1 10	
blue	56.340.003	1	
white	EC 240 00E	10	
white	56.340.005	1 10	



Drive Disc

incl. 5 diamond segments grit 20 Diamond disc for sanding machine; With order let us know your machine type (Columbus, Nilfisk, Numatic etc.)

50.400.001



Diamond segment

plates 40x10x10mm mesh 16/20

hard bond for soft	concrete	
Korn 16/20	55.710.016	1
Korn 30/40	55.710.030	1
Korn 60/80	55.710.060	1
medium bond for r	nedium hard concrete	
Korn 16/20	55.720.016	1

 Korn 16/20
 55.720.016

 Korn 30/40
 55.720.030

 Korn 60/80
 55.720.060

soft bond for hard concrete

 Korn 16/20
 55.730.016
 1

 Korn 30/40
 55.730.030
 1

 Korn 60/80
 55.730.060
 1

very soft bond for very hard concrete Korn 16/20 55.740.016

 Korn 16/20
 55.740.016
 1

 Korn 30/40
 55.740.030
 1

 Korn 60/80
 55.740.060
 1



PKD Segment

2 PKD tooth and one diamond segment specially used for difficult substrate e.g. carpet foam, glue, coatings

55.810.000 1





Item	Item-No.	Package/Piece	Piece/Pair
Diamant Saw Blade Lase for concrete substrate	er Welded		
Diamant equiped: 2,2 x 7 Ø 115 mm	7 mm 51.115.031	1	
Diamant equiped: 2,2 x 7 Ø 125 mm	7 mm 51.125.031	1	
Diamant equiped: 2,3 x 7 Ø 180 mm	7 mm 51.180.031	1	
Diamant equiped: 2,4 x 7 Ø 230 mm	7 mm 51.230.031	1	
Diamant Saw Blade Lase Substrate asphalt, screed	er Welded		
Diamant equiped: 2,3 x 7 Ø 115 mm	7 mm 51.115.032	1	
Diamant equiped: 2,3 x 7 Ø 125 mm	7 mm 51.125.032	1	
Diamant equiped: 2,4 x 7 Ø 180 mm	7 mm 51.180.032	1	
Diamant equiped: 2,5 x 7 Ø 230 mm	7 mm 51.230.032	1	
Diamant Saw Blade Lase Substrate concrete; für 20			
Ø 300-1200 mm	51.000.xxx		
Substrate asphalt; für 20- Ø 300-1200mm	65 PS 51.000.yyy		



Tornado for resins, concrete	and plastic substrates	
Pot hight incl. 5 mm	Segment 21 mm	
Diameter		
115 mm	55.115.052	1
125 mm	55.125.052	1
Pot hight incl. 5 mm	Segment 26 mm	
150 mm	55.150.052	1
Pot hight incl. 5 mm Diameter	Segment 31 mm	
180 mm	55.180.052	1







1

for concrete substrate

Economy Qualität Pot hight incl. 5 mm Segment 20 mm

Diameter

115 mm 55.115.011 125 mm 55.125.011

Pot hight incl. 5 mm Segment 26 mm 180 mm 55.180.011

Standard Quality

Pot hight incl. 5 mm Segment 20 mm

Diameter

115 mm 55.115.021 1 125 mm 55.125.021 1 150 mm 55.150.021 180 mm 55.180.021

Pot hight incl. 5 mm Segment 31 mm

Diameter

150 mm 55.150.022 180 mm 55.180.022 230 mm 55.230.022

Premium Quality

Pot hight incl. 5 mm Segment 20 mm

Diameter

115 mm 55.115.221 1 125 mm 55.125.221 1 150 mm 55.150.221 1 180 mm 55.180.221 230 mm 55.230.221

Pot hight incl. 5 mm Segment 31 mm

Diameter

150 mm 55.150.222 1 180 mm 55.180.222 1 230 mm 55.230.222



with polycristaline diamant (PCD)

to remove a glue, coatings, paints and sealer

to smoothen screed and young concrete up to grain size 8 mm

Diameter

115 mm 55.115.061 125 mm 55.125.061 55.150.061 150 mm





125 mm

180 mm

Floor Grinding Disk



Item	Item-No.	Package/Piece	Piece/Pair	
Turbo S / Swirl				
for concrete substrate				
9 segments at diameter	115 and 125 all o	ther 12 segments		
Pot hight incl. 5 mm Seg	ment 18 mm			
Diameter				
110 mm	55.115.422	1		
125 mm	55.125.422	1		
180 mm	55.180.422	1		
18 segments at 125; 24 segments at 175mm				
Pot hight incl. 5 mm Segment 18 mm				
Diameter				

55.125.424

55.180.424



sintered for dry and wet purpose for concrete substrate Premium Quality, Segment Size 40 x 10 x 10 mm Diameter 250 mm Segments 10 55.250.031 1 Segments 20 55.250.231 Diameter 300 mm Segments 12 55.300.031 Segments 24 55.300.231 Supreme Qualität, Segmentabmessung 40 x 10 x 10 mm Diameter 250 mm Segments 10 55.250.131 55.250.232 Segments 20 1 Diameter 300 mm 55.300.131 Segments 12 1 Segments 24 55.300.232 **Substrate Asphalt, Screed and Green Concrete**

Premium Quality, Segment Size 40 x 10 x 10 mm

Joint Grinder





to cut joints into floo	r or wall		
width 6,4 mm			
Diameter			
115 mm	55.115.051	1	
125 mm	55.125.051	1	
180 mm	55.180.051	1	
230 mm	55.230.051	1	
Joint Cleaner			

to clean joints from dirt and other materials usable conditional for concrete and screed

Diameter 125 mm		
width 6,4 mm	55.125.151	1
width 8,0 mm	55.125.251	1
Diameter 125 mm		
width 10,0 mm	55.125.351	1





Piece/Pair





Item Item-No. Package/Piece

Knee Pad

articulated, inside antistatic cellular rubber-profile, outsideslip resistant profile, with elastic folds

pivoted 80.420.001 1 Pair



Knee Pad

with flexible, non marking cap

flexible 80.430.001 1 Pair



Latex Glove

cotton glove coated with latex , solvent resistant open back style with cuff or knitted wrist

Size 10	60.200.010	12 Pair
		120 Dair

knitted wrist 60.210.010 12 Pair 120 Pair



Nitril Coated Glove

high flexible nitril coated tricot glove, open back style,

Ln	hotti	wrist
KII	ILLEU	WHIST

Size 9	60.300.009	12 Pair
		144 Pair
Size 10	60.300.010	12 Pair
		1// Dair

Size 11 60.300.011



Nitril Coated Glove

high flexible nitril coated tricot glove, open back style, knitted wrist

knitted wrist

Size 9	60.310.009	12 Pair
		144 Pair
Size 10	60.310.010	12 Pair
		144 Pair



high flexible nitril coated tricot glove, open back style, with cuff for easier to puton and take off

Size 10	60.500.010	12 Pair
		144 Pair




























Hand Cleaner

special cleaner for resins, sensational cleaning performance

250 ml 98.000.511 1000 ml 98.000.011 1

Skin Maintaining Lotion

Lotion for skin regeneration,

containing bee wax and natural oel, silicon free

250 ml 98.000.002 1

Cover Foam

protect hand from dirt, reduces hand sweatting in gloves, reaches for approx. 150 applications

100 ml 98.000.003 1

Cotton cleaning cloth

mixed

10kg box, price per box

according to DIN 61650

many-colored 98.800.010 white 98.801.010

Non-woven cloth

10kg box approx. 500p, price per box

Size approx.

40 x 40 cm 98.810.010

Scrubs in a bucket

72 pieces with sensational cleaning performance

Bucket 98.900.001 6

Eye Rinsing Bottle

200ml, with 0,9% Na-Solution, durable 3 years max. rinsing time 4 min

> 94.000.200 1

Protection Bag

for eye rinsing bottle Art. Nr. 94.000.200 incl. straps for belts attachment

94.001.200



Item Item-No. Package/Piece Piece/Pair **Protective Helmet** according EN, 6 internal strap support and sweat band, rainwater gutter, prepared for ear and face protection, weight approx. 337g 80.000.001 blue 1 **Safety Glasses** also suitable for wearer of eyeglass 80.100.001 normal 1 anti fog coated 80.100.002 1 **Safety Glasses** Nylon, glass size: 2,5x2" (62x52mm) 80.200.001 1 **Panorama Safety Glasses** extremly light weight, scratch resistant and antistatic polycarbonate glass 80.200.002 1 **Ear Protection Capsule** european product, high quality, weight approx. 160g, adjustable to any required size SNR-Value 23 dB 80.300.001 1 **Earplugs** SNR: 28dB 80.300.010 10 250 **Earplugs with Cord** for long term use SNR: 32 dB 80.300.050 5 50





Item Item-No. Package/Piece Piece/Pair

Dust Respirator

no respiratory protection

92.100.001 50

€



Dust Respirator FF P1

no breathing filter,

can be used in concentrations up to 4x the exposure Standard, it meets the requiremnts of EN 149/2001 ClassP1

92.200.001 20



Dust Respirator 3M FF P1

Standard: EN149:2001 FFP1; Approval: CE Marked Maximum use level: Assigned Protection Factor: 4 x OEL (Nominal Protection Factor 4 x OEL)

92.200.104 10



Dust Respirator 3M FF P2

Standard: EN149:2001 FFP2; Approval: CE Marked Maximum use level: Assigned Protection Factor: 10 x OEL (Nominal Protection Factor 10 x OEL)


92.200.110 10



Dust Respirator 3M FF P1

Comfort Class; Standard: EN149:2001 FFP1; Approval: CE Marked Maximum use level: Assigned Protection Factor: 4 x OEL (Nominal Protection Factor 4 x OEL)

92.200.204 10



Comfort Class; Standard: EN149:2001 FFP2; Approval: CE Marked Maximum use level: Assigned Protection Factor: 10 x OEL (Nominal Protection Factor 10 x OEL)

92.200.210 10



Half Mask Respirator

The 3M 6000 Series half masks are reusable respirators designed for low maintenance and maximum simplicity and comfort.

Use filter Art. Nr.: 93.000.001/002

 Size M
 92.300.101-M
 1

 Size L
 92.300.101-L
 1









Item	Item-No.	Package/Piece	Piece/Pair

Dungarees

Colours: blue, red, green, white approx. 290g/m2, 100% Cotton

Blue: Art. Nob Green: Art. Nog	Red: Art. Nor White: Art. Now	
Size		
44	90.000.044-	1
		10
46	90.000.046-	1
		10
48	90.000.048-	1
		10
50	90.000.050-	1
		10
52	90.000.052-	1
		10
54	90.000.054-	1
		10
56	90.000.056-	1
		10
58	90.000.058-	1
		10
60	90.000.060-	1
		10

Other Sizes on request, Intermediate Sizes available, minimum order 10 pcs



Colours: blue, red, green, white approx. 290g/m2, 100% Cotton

Blue: Art. Nob Green: Art. Nog	Red: Art. Nor White: Art. Now	
Size 44	91.000.044-	1
46	91.000.046-	10 1 10
48	91.000.048-	1 10
50 52	91.000.050- 91.000.052-	1 10 1
54	91.000.054-	10
56	91.000.056-	10 1 10
58	91.000.058-	1 10
60	91.000.060-	1 10

Other Sizes on request, Intermediate Sizes available, minimum order 10 pcs

Jackets to the trousers

91.000.0xx-y	1
	10







Item	Item-No.	Package/Piece	Piece/Pair
PE Overall white, with cowl, fitted wit	h zip fastener		
Size XL	90.000.XL	1 50	
XXL	90.000.XXL	1 50	



PE TrousersPPSoft 42g/m2, air-permeable, elastic waits at waist and feet

Size XL	90.100.XL	10
Size XXL	90.100.XXL	10

Item Item-No. Package/Piece Piece/Pair

Head Hood

perforated Viscosefleece, white, latexfree bungee cord(anti allergic) very air-permeable hood, $\,\emptyset\,$ 53cm

92.010.053

100



PP Armprotection

Polypropylenfleece, $30\ g/m^2$ for splash protection, air-permeable

45 cm

92.010.001

10 30



PE Protection Boot

splash protection of shoes and trousers during dearation, primering or sealing

92.000.001

10 30



PP-CPE Protection Shoe 25 cm

for walking on new floors to protect against scratching

92.000.003

50

100



Balance Digital

Supporting Plattform 32x38cm, weighing range up to 75 kg; up to 25kg in 5g steps from 25kg in 10g steps; TARA Funktion;

Automatic shutdown (idle) Individually adjustable (deactivate; 15min, 30min, 45min, 60min); electric or battery powerd (4x1,5V AA)

99.000.001









Collomatik CX 40 (1200 Watt)

Universal professional hand mixer to satisfy higher demands. Powerful motor, 2-speed gear unit

M14 Port 00.020.102 1 with Hexafix-port 00.020.028 1

Collomatik CX 60 (1600 Watt)

A top-class hand-held mixing machine for heavy-duty and demanding professional applications

M14 Port **00.020.151** with Hexafix-port **00.020.039**

Collomatik CX 44 DUO

Infinitely adjustable speed control; 2-speed gear unit for optimal torque processing; HEXAFIX® quick-release coupling; comes with MKD 140 HF mixing tools

 with Hexafix-port
 00.020.251
 1

 Mixing Tool for Hexafix
 00.044.080
 1

 for M14
 00.044.030
 1



Big Elephant (1200 Watt)

with stirrer MK 140 (M14); 2-speed gear unit (150-400 rpm and 250-650 rpm) and variable speed electronics; due to new starting technologie splashing is avoided; for volume up to 50 Kg (14 gallons)

00.012.125

Big Elephant (1800 Watt)

with stirre MK 160; 2-speed gear unit, (150-350 rpm and 350-650 rpm) and variable speed electronics; due to new starting technologie splashing is avoided; for volume up to 100 Kg (28 gallons)

00.012.180 1



Eibenstock EZR 21 S (1150 Watt)

Double Paddle Mixer with mixing tool, 2-gear engine

 00.007.732
 1

 Mixing Tool 250mm
 00.031.610
 1

 Mixing Tool 140mm
 00.031.620
 1



Mixing Stirrer

Ø 140, height 17

Ø 160, height 21

The particularly rugged professional mixing tool for tough day-to-day building site service.

M14, length 590 mm		
Ø 120, height 14	00.031.324	1
Ø 140, height 17	00.031.326	1
Ø 160, height 21	00.031.327	1
for Hexafix Slot, leng	th 590 mm	
Ø 120 height 14	00 040 114	1

00.040.115

00.040.116

		€
Item	Item-No. Package/Piece	Piece/Pair

This mixing tool generates high shear forces for a powerful suction

Notable for good homogenization of fillers, as well as adhesives and sealants, bitumen coatings, epoxy-resin compounds, etc. easy to clean



Slot M14 Length 590 mm	1	
Mixing Paddle KR 120	00.031.024	1
Mixing Paddle KR 140	00.041.635	1
Mixing Paddle KR 160	00.041.636	1



Stirrer	Disk	with	Ring


Ø 140 mm 600 mm length, Slot M14

effect and prevention of lump formation.

00.033.140 1

Ø 160 mm 600 mm length, Slot M14

00.033.160 1



Stirrer Disk

Ø 80 mm 500 mm length, for drilling machine

00.031.080

Ø 120 mm 500 mm length, for drilling machine

00.031.120

Ø 150 mm 590 mm length, Slot M14

00.031.150



Stirrer Spiral without ring

Ø 120 mm 600 mm length; cage high 110 mm, for drilling machine

00.041.247

Ø 100mm 400 mm length; cage high 100 mm, for drilling machine

Korbhöhe 10 cm

00.041.248

 \emptyset 85 mm 500 mm length; cage high 90 mm, for drilling machine 00.031.085

Ø 100 mm 500 mm length; cage high 90 mm, for drilling machine 00.031.320



Elongations

for Stirrer, Slot M14

15 cm	00.032.215	1
25 cm	00.032.225	1
40 cm	00.032.240	1



Road Sweeper

Width 77cm 4 year Guarantee, perfect for sweeping off sand

99.600.075





Item Item-No. Package/Piece Piece/Pair

Bucket Carrier

comfortable emptying of mixing buckets

46.000.001



Bucket Carrier

cheap solution for transporting mixing buckets without bucket

46.100.000 1



Plastic Construction Bucket

black

12 Liters 99.100.012 5



Mixing Bucket

30 Liter

Height 37 cm 99.200.030 5

75 Liter

Height 53 cm 99.205.075 1



Item	Item-No.	Package/Piece	Piece/Pai

Mixing Barrel

black

53 x 44,5 Diameter inside; 32 cm high inside

65 Liter 99.200.065 3

60 x 50,5 Diameter inside; 33 cm high inside

90 Liter 99.200.090 3



Mixing Barrel

white

54 x 44 Diameter inside; 32 cm high inside

65 Liter 99.205.065

Mixing Barrel

with alu-ring

Measure outside: above/below: 650/500x400mm

innside: 600/490x380mm

Colour: nature Material: PE-HD

Temperature resistance: between 30°C up to +50°C short term

for cleaning up to +90°C

80 Liter 99.200.080 1



Evacuation Cock

grey cast iron 2" 99.500.102 1

Rubber seal 2"

99.510.102



Evacuation Cock

Polyethylen 2" 99.500.202 1

Polyethylen 3/4" 99.500.203 1



Barrel Plug Key

99.500.301 1



 $\begin{tabular}{lll} \hline & & & & & \hline \\ Item & & Item-No. & Package/Piece & Piece/Pair \\ \hline \end{tabular}$

Barrel Cart

for transporting 200l barrels on site

99.500.401



Barrel Dump

Barrel Tip-Support for lifting, storing and filling of 200l barrels, size 68x80cm

99.500.410 1



Trolley

Aluminium-steel-construction with aluminium shovel and high-grade plastic parts.

Air filled wheels. Hubs with needle bearings. Comfortable anti slip pull bar. Elastic adjusting straps for saving the transport goods. Shovel and wheels hinged with one grip. Retractable gripping bars.

Loading capacity 250 kg, Length of shovel 45 cm; width of shovel approx 60 cm; Total width approx. 66 cm; net weight 12,6 Kg

Dimensions folded: high approx. $85\ cm$; width approx. $66\ cm$; depth approx. $13\ cm$

Dimessions opend: hight approx. 174 cm; width approx. 66 cm; depth approx. 74 cm

99.500.420 1

Dimension (mm) Diameter x Length	Item No.	Unit 100	500	€/Piece 1000
Packer HK: with high pressure NK: with low pressure HF: with high pressure NF: with with low pres	round nipple e pan head nipple			
8 x 85 Packer galvanized ste 8 x 85 other Length on reque	00.008.070 HK 00.008.070 NK 00.008.070 HF 00.008.070 NF		round nip	ple
10 x 85 Packer galvanized ste	el 10 x 85 mm with 00.010.070 HK 00.010.070 NK 00.010.070 HF 00.010.070 NF		round nip	ople
10 x 110 Packer galvanized ste	el 10 x 110 mm wit 00.010.110 HK 00.010.110 NK 00.010.110 HF 00.010.110 NF		e round n	ipple
13 x 85 Packer galvanized ste	el 13 x 85 mm with 00.013.070 HK 00.013.070 NK 00.013.070 HF 00.013.070 NF		round nip	ople
13 x 110 Packer galvanized ste	el 13 x 110 mm wit 00.013.100 HK 00.013.100 NK 00.013.100 HF 00.013.100 NF		e round n	ipple
16 x 100 Packer galvanized ste	el 16 x 100 mm wit 00.016.100 HK 00.016.100 NK 00.016.100 HF 00.016.100 NF		e round n	ipple





Pan Head Nipple Ø 16 mm Head

High Pressure

Low Pressure

00.300.201

00.300.202



Dimension (mm) Item No. Unit €/Piece
Diameter x Length 100 500 1000

Mouth Piece

with inside thread M 10x1, for round head nipples

00.400.101



Slide Coupling Lateral

with inside M 10 x 1, for pan head nipples

16 mm 00.400.201

Ersartzteilset für Schiebekupplung mit Dichtungsgummi

16 mm 00.400.221



Flexible Whip

both ends with M10 thread, max pressure 850 bar acc. DIN 1283

8 x 300 mm, 00.400.501

other sizes on request



Reciprocating pump

500 ml 00.912.602

1000 ml 00.912.601



Item Item-No.

Package/Piece

€ Piece/Pair



Psychrometer with external temperature sensor, memory, RS-232 Psychrometer (Dew point) with data storage and type-K temperature probes

This psychrometer can measure different environmental conditions, in addition to also being able to simultaneous display the surface temperature of walls and products with its external temperature sensor. It can also calculate dew point and wet bulb.

It also has a memory to stores up to 99 measurements.

- · Real time clock and date
- · Memory stores up to 99 readings
- sensor and surface temperature of walls or food with its external sensor
- · Determines dew point and wet bulb
- ISO Certificate (optional)

Technical specifications

Measurement range: Temperature (internal) -20 to 50 °C

Relative humidity 0 to 100 % r.h. Temperature -21.6 to 50 °C

Dew point temperature -78.7 to 50 °C

Temperature (external) -20 to 70 °C (depending on sensor)

Resolution: Temperature 0.1 °C Relative humidity 0.1 %

Accuracy: Temperature ±0.6 °C Relative humidity ±3 %

Response time approx. 60 s Humidity sensor endurance sensor Memory stores up to 99 readings

External temperature- cable of 1.1 m, adjustable sensor with a type K beat wire temperature /dimensions with handle: 15 cm Power supply 4 AA batteries (1.5 V)

1

Operating temperature -20 to 50 °C / 0 to 100 % r.h. Dimensions 44 x 57 x 230 mm

Weight 200 g

Contents: Psychrometer (Dew Point), Software, Data Cable,

battery back, users manual

85.100.320

Humidity tester for building materials

to measure humidity in materials of construction (concrete, etc.) The humidity tester for building materials is used to measure humidity of concrete. This humidity tester for building materials use a measurement procedure works according to both the dielectric constant principle or the high frequency principle. To get accurate results with the humidity tester for building materials, you will only need to select the concrete type is going to be tested and put the electrodes on the concrete surface. Electromagnetic waves penetrate to a 50 mm depth, so the measurement results will be the mean value calculated within the 50 mm of surface. At this link you will find other humidity tester for building materials provided with interface, memory and software for data to be transferred to a PC or a portable computer.

- Measuring depth of 50 mm approx.
- · Results are showered in few seconds.
- Any preparation is required.
- · 3 positions LCD display.
- · Direct and safe use in situ.
- Battery indicator.

Technical specifications

Measurement range 1 to 8 % of absolute moisture Accuracy ±0.7 %

Resolution 0.1 %

Measurement depth approx. 50 mm Display 3.5 digit LCD Power 9 V battery pack Dimensions 165 x 80 x 30 mm

Weight 500 g

Contents Moisture meter, battery back, carrying case and users

manual

85.100.300







Item

€

Balance to

Item-No. Package/Piece

Piece/Pair

measure moisture

The Balance has been specially designed for the use in industry or in the laboratory. This balance provides a quick and accurate method to measure moisture content and dry weight analysis of a wide range of products and materials. The users manure will provide you with advice and numerous practical examples. The two quartz halogen lamps (200W each) provide constant, even drying of the sample at a temperature pre-selected by the operator.

Only a small sample needs to be placed on the balance, then close the cover, press the button and read the result (content of humidity; dry content). This instrument is the perfect tool in determining moisture and dry content weight accurately. You will be able to determine the humidity of materials of a range of materials, such as plastic, wood pellets, pharmaceutical substances, tobacco, tea, cereals, etc.

Checking moisture and dry content can be done three different ways: Automatic: drying material until it has a constant weight Semi-automatic: drying stop when loss per unit of time goes below theoretical value Manual: adjusting the timer between 2 minutes and 9 hours and 59 minutes

The balance includes:

RS-232 adaptor to transfer data to a PC External calibration function 230 V power supply

Technical specifications

Tara range Full 2 x 200 W quartz halogen heaters +50 to +160 $^{\circ}\text{C}$

Heating Temperature range

Drying time 2 min to 9 h 59 min (adjustable by 1 second increments) automatic, semi-automatic, manual Drying modes

Drying sequence Indication after drying

pre-selected on the display using a diagram moisture [%] / dryness weight, weight before dryness [%] ATRO / date and time

Memor < 160 (to allow user to produce drying curves for specific materials)

Display Calibration large display with multilingual menu external calibration (with optional calibration weight)

Interface RS-232

Operating conditions +18 to +30 °C Power 230 V / 50 Hz die cast aluminium Ingress protection Dimensions IP 54

Weight approx

Weight range, Max 100g, Modell 100:

0 to 100 % absolute humidity 0 to 0 % dry content


235 x 245 x 260 mm 8 kg Readability Repeatability Pan size

0,001g 0,01% 0,01g 0,02% Ø 90 mm

85.100.100 1

Software kit for humidity balance

85.100.110 1











€ Item Item-No. Package/Piece Piece/Pair

Fiberglass round filters

85.100.130 1




Aluminium sample pans Pack of 50 aluminium sample pans

85.100.140 1



Item Item-No. Package/Piece Piece/Pair



LDM 50 laser distance meter handheld distance meter for accurate measurements up to 50 m / with several functions: addition / subtraction / calculation of surfaces / calculation of volume/ Pythagoras's test / suitable for quick, accurate and reliable measurements.

The LDM 50 laser distance meter measures quickly and accurately any distance. The LDM 50 laser distance meter is a very easy-to-use device suitable for any measuring work. Just by pressing one button of our laser distance meter you will be able to determine within seconds measuring results. Thanks to the high accuracy of the laser you will be able to perform professional measurements. The PCE-LDM 50 laser distance meter will measure any surface with the highest accuracy, no matter if they are tiles, carpeting or parquet. The LDM 50 laser distance meter is very useful when calculating the amount of material required as for instance in a floor. In areas with many angles and corners, you will quickly obtain accurate measured values, as the LDM 50 distance meter calculates these values and gives a surface as a result.

Delivered with a solid carrying case

- Addition
- Subtraction
- . Max. and Min. measurements.
- · Continuous measurement
- · Distance measurement
- · Calculation of surfaces
- Calculation of volume
- · Pythagoras's test
- Large LCD display
- The laser pointer shows accurately the measured point.
- Solid enclosure
- . Memory for the last 20 values.
- Auto shut-off to protect battery life

Technical specifications

Measurement rang Accuracy 0.05 m to 50 m ±1,5 mm Resolution 1 mm Laser class 2 Laser type 635 nm,<1 mW Auto shut-off after 180 s Continuous measurement (tracking function) Addition / subtraction yes yes Pythagoras's test (2 points) Protection lp54 yes, the last 20 values 2 x AAA batteries Memory up to 5000 measurements 110 mm x 45 mm x 27 mm Battery life

Weight 135 g Storage temperature -10 ... 60 °C Operating temperature 0 ... 40 °C

Delivery contents

1 x LDM 50 laser distance meter, 2 x AAA batteries, 1 x carrying case, 1 x hand subjection and user's manual.

85.200.050

1



The laser fixed target makes it possible a better reflection from a long distance to the specific target. (it is recommended from 40-50 metres).

85.200.055







Item Item-No. Package/Piece Piece/Pair

Disto DXT

Laser Distancemeter Leica Disto DXT

The Leica DISTO? DXT is the only laser distance meter, which is protected against jet water and is absolutely tight against dust - according to IP 65. This ensures, that it operates precisely, even at very unpleasant conditions.

Dust-proof and jet water protected IP65

The housing and keypad are specially sealed against water and dust. Cleaning under running water is no problem.

The sensitive measuring elements are protected by solid rubber parts. The Leica DISTO? DXT is therefore particularly resistant and endures drop tests from 2m height.

Multifunctional end-piece

Whether measuring out of corners, slots or from edges, with this endpiece you are prepared for all measuring situations. The instrument detects the endpiece automatically, which helps you to avoid expensive measuring errors.

Functionality

The Leica DISTO? DXT has a diverse range of functions, e.g. addition, subtraction, area, volume, Pythagoras, continuous measurement and minimum/maximum measurement.

Technical specifications

Measuring range 0.05 to 70 m Typ. accuracy ± 1.5 mm Sealed keypad Easy to clean under running water. Solid rubber housing Endures drop tests from 2 m height. Hard-wearing, illuminated display Measured values can be read, even in the dark. Flip-out end-piece with automatic detection Minimum and maximum measurement function Room dimensions Continuous measurement Simple and quick staking out. IP65

85.200.070



Item

Item-No.

Package/Piece

Piece/Pair



Odometer

The odometer can measure up to 9999,9 meters. Only a person can comfortably use the odometer for long-distance measurements. The odometer has a robust construction to operate in harsh environmental conditions. The wheel of the odometer automatically measures up to 9999,9 meters. The odometer is the ideal instrument to measure cables, pipelines, fences, construction works, industrial areas, sports installations, agricultural plants, etc. The odometer can automatically measure up to 99999,9 meters and allow both forward and backward measurements.

85.200.100

1



Concrete testing hammer

The handheld mechanical hardness meter for testing concrete hardness meter for concrete is easy to use and is fundamentally used in the construction industry as well as other industrial sectors (testing for Wickel hardness of rolls in commodities). This hardness meter in the form of a hammer device for testing concrete is based on the Schmidt principal of measurement. Testing is always done under the same test energy of 2207 J. The kinetic energy of the rebound is givne by the device as the measurement of the hardness of concrete, of the pressure upon the surface or as the resistance to pressure (kg/cm² or its conversion to N/mm²). The quality of concrete is useful in understanding the material's resistance to pressure, as an orientating value for testing the load capacity and durability of concrete constructions. Resisitance to pressure is represented as a series of numbers and letters, for example: B 25 indicates that the material is normal concrete with a resistance to a pressure equal to 25 N/mm². Different readings exsist up to the highest class of resistance which is indicated as B 55. With our hardness meter you will be able to easily and accurately classify concrete. The hardness meter comes calibrated from the manufacturer but an ISO calibration certificate can be ordered seperately at extra cost

85.300.225





Pull Off Tester (manuell

The portable, hand-operated PosiTest Pull-Off Adhesion Tester measures the force required to pull a specified test diameter of coating away from its substrate using hydraulic pressure. The pressure is displayed on a digital LCD and represents the coating's strength of adhesion to the substrate. In accordance with ASTM D4541, D7234, ISO 4624 and others, the PosiTest evaluates the adhesion (pull-off strength) of a coating by determining the greatest tensile pull-off force that it can bear before detaching. Breaking points, demonstrated by fractured surfaces, occur along the weakest plane within the system consisting of the dolly, adhesive, coating layers and substrate.

85.400.000 1



Pull Off Tester

The portable, hand-operated PosiTest Pull-Off Adhesion Tester measures the force required to pull a specified test diameter of coating away from its substrate using hydraulic pressure. The pressure is displayed on a digital LCD and represents the coating's strength of adhesion to the substrate. In accordance with ASTM D4541, D7234, ISO 4624 and others, the PosiTest evaluates the adhesion (pull-off strength) of a coating by determining the greatest tensile pull-off force that it can bear before detaching. Breaking points, demonstrated by fractured surfaces, occur along the weakest plane within the system consisting of the dolly, adhesive, coating layers and substrate.

85.400.100

Measure head Ø 20 mm Set with 10 pieces	85.400.220	1
Measure head Ø 50mm set with 4 pieces	85.400.220	1
Set Screed for heavy coatings e.g. scre	ed.	
	85.400.260	1
Set for 50 mm		
	85.400.270	1
Special glue 2 komp. Glue for measure h	neads	
	85.400.280	1
Software for pull off tester For reading, writing datas for	r rom pull off tester. Incl. RS-232	cable.

85.400.160

85.400.170

Adapter RS 232 to USB

conecting PC to pull off tester (plug and play)

Item

Item-No.

Package/Piece

Piece/Pair



Cable Detector

With the cable detector you can detect voltage lines up to 400 V in circuits and free-voltage lines. The cable detector can locate cables, lines, circuits, short circuits, ground as well as test protective tubing and coaxial cables. To perform these functions, it is not necessary to disconnect the power source or to disconnect the power to the cable being tested. The location can be carried out in ground, concrete walls and brick walls by the cable detector. Cable detection system is composed of a signal generator for active lines and a transmitter for cables without current such as a receiver. The signal generator feeds high frequency electro-magnetic signals through the lines being tested. These signals are converted at the end of the cable, into acoustic or optical signals by the receiver. The intensity of the signal is the standard used for locating the line. In the signal generator both the signal power and the searching channel can be regulated. The cable detector can simultaneously work with diverse transmitters without any interference between them

85.500.010

1



Multimeter


The multimeter, which is like a pen is size and shape, is a multimeter suitable for daily use. It multimeter comes with alligators clips and an extension for measurement points, allowing the multimeter to be used in places that are normally difficult to access. The ability to use it in one hand and the data hold function make this an easy multimeter to operate. All measurement ranges, such as voltage (AC/DC), resistance, diode test, continuity test can be operated by a single finger pressing a button which activates the controls within. Such properties are important to technicians working in the sector for installations and machinery

85.500.001



Item

€ Item-No. Package/Piece Piece/Pair



Testboy 40 Plus

Our Testboy 40 Plus combines two practical functions in a single device. It reliably displays AC and DC voltages in the range 6 to 400 V. In addition, the electronics facilitate determining the phase against the protective earth conductor

A distinguishing characteristic of the Testboy 40 Plus is its user friendly design. The robust housing guarantees long-term reliability and has gained the approval of many customers working in the demanding electrical and tool making sectors.

The combination of materials used for the high-quality housing and the rubber grip underline the professional appearance of this instrument.

Absolute safety in perfomance - AC and DC voltage tests with polarity indication.

Your benefits: 5 year manufacturer's warranty IEC/EN 61243-3 (DIN VDE 0682-401)

85.500.040



Testboy LCD Plus

Thanks to its wide performance spectrum the Testboy Profi LCD Plus is one of the more sought-after products in our assortment.

The Testboy Profi LCD Plus combines the following 12 functions in a single device:

Displays AC and DC voltages from 6 to 1000 V

Single-pole phase testing

Two-pole phase sequence testing

Continuity testing up to 150 ohms (acoustic)

Resistance testing up to 2000 ohms

Diode testing

Data Hold function

Illuminated display

Two-button fault current/RCD test

LED torch (white)

Removable 4mm test tips adapter

Auto power Off

The automatic power off function extends the life of the batteries.

The LC display is a particularly professional feature of this instrument that makes it easy for the service or installation technician to display the phase and phase sequence. An acoustic signal is emitted to signalise a hazardous voltage when a 35V AC/DC voltage or above is detected. Pushbutton load connection prevents unwanted tripping of the RCD, and ensures measurements of the protective earth conductor can also be undertaken. Even when used daily the robust construction as well as the dust and waterproof housing guarantee a long service life. The test tips are protected by a removable cap that in turn is attached to the device.

Your benefits:

5 year manufacturer's warranty IEC/EN 61243-3 (DIN VDE 0682-401)

€
Package/Piece Piece/Pair

1

Item-No.

85.500.100

Pyrometer

Item

The pyrometer is ergonomic and easy to transport. This light infrared pyrometer is attractive due to its size and its accuracy thanks to a visible laser pointer. It pyrometer was designed for industrial use and for professionals working in inspection and maintenance of heating systems, ventilation systems, air conditioning units, in the automotive industry, for electrical systems and fuse boxes. The pyrometer can be used in adverse conditions. It has a backlit LCD. The pyrometer has a visible laser to quickly and accurately target the area to be measured allowing for measurements to be taken at certain distances if the object being measured it hot or difficult to access. The emissivity is fixed at 0.95 and covers 90% of possible measurements taken.

85.700.010

1





Wallscanner

The multifunction wall scanner can be used for any diverse applications. The multifunction wall scanner can locate wood, metals and low voltage lines. The PCE-STM 3 multifunction wall scanner finds both the edge and the centre (Center Vision) of wood beams and metallic reinforcements. The multifunction wall scanner is easy to operate thanks to the LCD menu. Acoustic and visual signals are activated when objects are detected to improve its use. With the multifunction wall scanner it is not necessary to perform drilling and fixing works to see what is behind roofs, walls or floors. With the multifunction wall scanner you will not waste time and money in additional works. The multifunction wall scanner has two levels available: bubble and laser to align pictures, tiles, etc... Laser beam is adjusted every 45°. The multifunction wall scanner is the ideal instrument for building works as well as for many other applications

85.800.003

ORDER



Billing Addr	ess	Delivery Address		
Company: _		Company:		
City: _		City:		
Street: _		Street:		
Phone: _		Phone:		
Name: _		Name:		
Date: _		Date:		
POS	Item No.	Item	Unit	Price
1				
2				
3				
4				
5				
6				
7				
8				
9				
10				
11				
12				
13				
14				
15				
16				
17				
18				
19				
20				

ORDER



Billing Add	ress	Delivery Address		
Company: _		 Company:		
City: _		 City:		
Street: _		 Street:		
Phone: _		 Phone:		
Name: _		 Name:		
Date: _		 Date:		
POS	Item No.	Item	Unit	Price
1				
2				
3				
4				
5				
6				
7				
8				
9				
10				
11				
12				
13				
14				
15				
16				
17				
18				
19				
20				

ORDER



Billing Address		Delivery Address	Delivery Address		
Company: _		Company:			
City: _		City:			
Street: _		Street:			
Phone: _		Phone:			
Name: _		Name:			
Date:		Date:	Date:		
POS	Item No.	Item	Unit	Price	
1					
2					
3					
4					
5					
6					
7					
8					
9					
10					
11					
12					
13					
14					
15					
16					
17					
18					
19					
20					



Terms of Sale and Delivery

I. Conclusion and subject of the contract

For our deliveries and other legal transactions, the terms and detailed below shall apply exclusively. Any other verbal and telegraphic arrangements, amendments, promises and collateral agreements shall be invalid unless by us in writing.

Purchase and payment terms stipulated by the Buyer shall not be accepted by us. The Buyer shall accept our Terms of Sale and Delivery even if they deviate from his usual purchase and payment terms.

Any objections raised to order confirmations must be submitted in writing without delay, at the latest within one week.

The legal inefficacy of individual provisions shall not render the entire contract invalid.

II. Offers

All offers made shall be without engagement unless expressly stated to the contrary, in which case they shall be binding for one month only calculated from the date of the offer, unless another period is specifically indicated.

Obvious errors, spelling mistakes and miscalculations shall be without commitment on our part. All particulars, such as dimensions, weights, illustrations, descrip-tions, assembly drawings and illustrations in sample catalogues, price lists and other reference materials shall be approximate only but determined as closely as possible, and shall not be binding on our part.

III. Prices

All prices are quoted ex works excluding Value Added Tax. Confirmed prices shall apply only if the confirmed quantities are bought. In the event of price increases occuring between the date of the order confirmation and the supply of the goods, we shall be entitled to adjust the prices accordingly.

IV. Delivery

Delivery shall be for account and risk of the Buyer, even if carriage-free delivery has been agreed. If free delivery has been agreed, the risk shall pass to the Buyer as soon as the vehicle arrives at ground level at the forwarding address, or at the point nearest to this address that can be reasonably reached by the vehicle. Selection of the transport route and means of the transport shall rest with us. Partial deliveries shall be admissible and shall be considered as independent deliveries. If the Buyer does not accept the goods in time, or if he fails to observe the call dates, we shall be entitled to effect the deliveries due, either in full or in part, or to put the goods into storage and invoice as delivered, to rescind, either in full or in part, or finally to demand compensation on the grounds of nonfulfillment. Disruptions caused by fire, strikes, lockouts, shut-downs, official measures, lacking supplies and force majeure which may prevent or impair the deliveries, shall entitle us, at our option, to rescind, either in full or in part or to postpone the deliveries accordingly without being liable for damages. Non-observance of delivery times does not release the Buyer from his obligation to accept the goods. For any damages due to a delay in at cost price. Returning packaging material shall be accepted and refunded only if specifically agreed upon. Insurance covering damage in transit, loss in transit and breakage shall only be taken out if expressly requested by the Buyer and shall be charged to him.

Any claims on the scope, amount, weight, dimensions, and kind of the goods must be made immediately but no later than three days after arrival of and prior to use of the goods. Claims concerning partial deliveries shall not entitle the Buyer to refuse acceptance of the entire delivery.

Notifications of defects must be made in detail and in writing and must be received by us within seven days of arrival of the goods. Claims in respect of hidden defects

must be made immediately on discovery of the defect, at the latest, however, within two months after receipt of goods. If defective goods have been deliver-ed, we shall be entitled, at our option, to reduce the price, make good the defect or supply faultless replacement. We shall be entitled to supply replacement even if this cannot be effected immediately. Any replacement shall be supplied at the earliest possible date. Any further claims by the Buyer on whatever legal grounds, especially with regard to redhibition and indemnification, shall be excluded.

We shall be under no obligations to acquire replacements from other sources.

No warranty whatsoever shall apply of the processing or use of the goods has already been commenced, or if the Buyer himself or any third party has carried out, or tried to carry out, repairs of our goods. The same shall apply to any goods which have been sold by the Buyer either before or after claims have been made. In the case of manufacturing defects our warranty shall be limited to the warranty given by our suppliers.

By negotiating a claim we shall not be considered as waiving our objections to the existence of a defect, to the obligations for the supply of replacement, or to the time limit and sufficiency of the claim.

VI. Return of goods

Goods delivered by us shall only be taken if agreement to this effect has been made and shall be returned in immaculate condition, carriage paid. Credits for returned goods shall be subject to a 10% deduction for costs incurrent. Returns to specially made goods, or goods procured at the specific request of the customer, shall be excluded. For returned goods with a net value less than EUR 50.-, no credit-notes will be made.

Unless agreed otherwise, our deliveries shall be paid for at once, at the latest 30 days after date of the invoice. All payments shall be made free of charge for us. Payments effected within 10 days of receipt of invoice shall be subject to a discount of 2 per cent, provided, however, all financial commitments have been met in full, including those for earlier deliveries. The discount shall be calculated based on the net invoice amount, after deduction of rebates, freight charges etc. Once payment of an invoice has become due i.e. at the latest 30 days from the invoice date, interest will be charged at a rate of 3 per cent above the base rate of the European Centralbank, not excluding the right to make further claims for default. The day of receipt of any payment shall be the day on which our account has been credited with the respective amount. Bills of exchange and cheques shall only be accepted subject to being honoured. Acceptance of bills of exchange shall be as security only, and shall not be considered as respite for payment. If our bankers decline to discount a bill of exchange, then payment in cash must be made immediately. Discounting and collecting charges shall be for Buyer's account. Liability for payment shall persist even if the Buyer has submitted claims, in particular in respect of defects. The warranty detailed under Paragraph V shall be given on the understanding that the Buyer has effected the payments due. The right to make setoffs and claiming a lien on goods shall be excluded. **VIII. Retention of Title**

All goods supplied by us under a delivery contract shall remain our property until payment in full has been made, or until cheques or bills of exchange have been honoured. In the case of a current account the retention of title shall be considered as security for our claim of the balance. The Buyer shall be entitled to legally sell the goods supplied and the goods manufactured from these. He shall be obliged to impose our condition of retention of title on his customers. Without our written consent the Buyer shall not be entitled to assign, pledge or transfer the title as security. When selling the goods supplied by us, the Buyer shall assign at that moment all claims against his customers, including ancillary rights and securities out of sale until all payments to us have been made in full, and this assignment shall be accepted by us.

If the goods are taken back on the basis of our retention of title or any other reason, the Buyer shall be obliged to return the goods to us free of charge and shall be liable for any undervalue. We shall be entitled to collect the goods when enforcing our right or retention of title.

IX. Place of performance and place of jurisdiction

Place of performance for deliveries shall be the place of the goods. Place of performance for all obligations on the Buyer's part shall be the location of our firm. Place of jurisdiction shall be the court competent for the location of our firm. This shall also apply to claims being filed by judgement note. The law of the Federal Republic of Germany shall apply. The provisions of the Hague Convention of 1964 on purchases and purchase contracts shall be excluded.

X. Validity

If one instruction will be invalid, the validity of the other instructions won't be touched herefrom.

MULTITOOL GmbH

Scheffelstraße 6 · 69234 Dielheim Fon +49 6222 7739733 · Fax +49 6222 75483 www.multitool.de · info@multitool.de

Representative Offices

Danmark: Mads Sørensen, Skovdalsvej 4, 8300 Odder Fon +45 40 429697. Fax +45 86 545376

Netherland: Henk Bols, Smirnoffstraat 12, 7903AX Hoogeveen Mobil +31 165 5750799, Fax +31 5282 76066

Swiss: Huber-Jeanneret AG, Jacques Huber, Tirolgasse 86, 5466 Kaiserstuhl Fon +41 44 8580391, Fax +41 44 8581187, Mobil +41 796 627794

Austria: REWA OG, Gerhard Wagner, Mitte 39, 9125 Kühnsdorf Fon +43 4232 89594, Fax +43 4232 89537, Mobil +43 664 2800263

Spain: Proesval S.L., Salvador González Cabo, C/Quinsana, 37, 46113 Moncadia Fon +34 961 39991, Fax +34 961 399833, Mobil +34 670 319575